

Features

- · Line voltage no drivers needed
- Interconnectable kits (3000K Warm White and 6400K Cool White) or custom cut lengths (2100K Ultra Warm White and 3000K Warm White)
- LED Flexbrite consumes only 1 watt per foot
- Dimmable 5-100%*
- UL Listed[†] for indoor and outdoor use
- 60,000 hours rated life

Available Colors







3000K 6400K

Dimming Options

- ELV (5-100%*)
- LED (5-100%*)
- CL (5-100%*)

Listing / Ratings[†]



LED Flexbrite Kits / Custom Cut


Easy to use flexible, dimmable, and economical LED rope light has UV inhibitor built into the PVC housing for use outdoors. Save 73% in running costs compared to incandescent rope light. LED Flexbrite last up to three times as long as incandescent rope. Choose from interconnect-able UL Listed kits or 150ft reels (UL listing is void if reel is cut).

Technical Information

LR-LED (Kits) / ULRL-LED (custom cut)
120V AC, 60Hz
2100K (UWW) / 3000K (WW) / 6400K (CW)
67+ (UWW) / 72+ (WW) / 75+ (WH)
1W per ft
See individual product
192 feet (kits) / 150 feet (custom cut)
N/A [†]
IP65** (uncut), void if cut
5-100%*
UL Listed† for indoor/outdoor use
60,000 hrs

^{*}Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers.

^{**}IP65 rated only when used with pre-attached molded power cord and end cap is either pre-attached or properly sealed with dialectric grease, silicone and shrink tube *UL Listing is void if product is cut





LED Flexbrite Kits



Warm White Kits 120V / 3000K / 72CRI / 32Lm/ft / 1/2" Diameter

LR-LED-WW-3 (3ft / 3W) **LR-LED-WW-9** (9ft / 9W) LR-LED-WW-15 (15ft / 15W) LR-LED-WW-30 (30ft / 30W) **LR-LED-WW-75** (75ft / 75W)



Cool White Kits 120V / 6400K / 75CRI / 34Lm/ft / 1/2" Diameter

LR-LED-CW-3 (3ft / 3W) LR-LED-CW-9 (9ft / 9W) LR-LED-CW-15 (15ft / 15W) LR-LED-CW-30 (30ft / 30W) LR-LED-CW-75 (75ft / 75W)

120V Kits Include: (1) Removable 5ft power cord with 1.6A inverter, (1) removable end cap, and (1) mounting clip per foot of rope

LED Flexbrite Custom Cut

Ultra Warm White Custom Cut 120V / 2100K / 67+ CRI / 30Lm/ft / 1/2" Dia.

ULRL-LED-UWW (36" increments)

ULRL-CONKIT-LEDSHELL

(Required for custom cut lengths) 120V UL2388 compliant power connection: (1) 5ft cord with 1.6A inverter with fused plug and end cap

Warm White Custom Cut 120V / 3000K / 72+ CRI / 32Lm/ft / 1/2" Dia.

ULRL-LED-WW (36" increments)

ULRL-CONKIT-LEDSHELL

(Required for custom cut lengths) 120V UL2388 compliant power connection: (1) 5ft cord with 1.6A inverter with fused plug and end cap

Custom Cut: Please allow up to 1 week for custom cut order processing and delivery

LFD Flexbrite Accessories



Linking Cable Jumper for LED Flexbrite Kits Interconnectable

LR-LED-EXT3 (3ft)



Mounting Track Clear plastic **RL-TRK-3** (3ft / Case of 40) RL-TRACK-4 (4ft)



Mounting Clips Clear plastic RL-CLIP/SCREW (10) Clips with (20) Screws LR-CLIP-20 (20) Clips with (40) Screws

